



# 7900 SERIES

# 450 LBS



## FEATURES

**KINGPIN:** 9/16" Rivet diameter  
**BALL BEARINGS:** 5/16" diameter upper race; 1/4" diameter lower race  
**BUSHING:** Sealed Precision Ball Bearings  
**AXLE&NUT:** 1/2" axle and lock nut

**FINISH:** Corrosion resistant bright zinc  
**HARDENED:** Sealed raceway  
**SPECIAL:** Automotive tire traction; full floor protection; quiet operation  
**PLY RATING:** Ply rating is 4, maximum PSI is 50

### EXCELLENT FOR:

- Uneven floors such as agricultural, institutional and industrial
- Quiet Cushion ride
- Shock and Vibration
- Prolonging equipment life
- Floor Protection
- Platform and Large stock trucks
- Food Service equipment
- Hotel Equipment



PNEUMATIC LUG



PNEUMATIC SAWTOOTH

### OPTIONS:

SLB Side Locking Brake

WHEEL			CASTER				PART NUMBER						
Diameter	Tread Width	Capacity Lbs.	Bearing Type	Swivel Radius	Overall Height	Tire Size	Tire Colour	Leg Spacing	Wheel Type	Swivel	Caster Weight (lbs)	Rigid	Caster Weight (lbs)
8"	2 1/2"	300	Precision Ball	6 1/4"	10"	2.50-4	Black	3"	Pneumatic (Lug)	S7908-A38H-PNC-PBB	6.58	R7908-A38H-PNC-PBB	5.70
10"	3 1/2"	350	Precision Ball	7 5/8"	12 1/2"	4.10/3.50-4	Black	4"	Pneumatic (Sawtooth)	S7910-A38H-PNC-PBB	7.69	R7910-A38H-PNC-PBB	7.32
12"	3 1/2"	450	Precision Ball	9"	14"	4.10/3.50-6	Black	4"	Pneumatic (Sawtooth)	S7912-A38H-PNC-PBB	11.25	R7912-A38H-PNC-PBB	10.00


\* All 8", 10" and 12" Pneumatics are fitted with a 3 pc. Split Rim / Bolt through flanged hub design

### FINISHES:

- 70?A Antique
- 70?PB Polished Brass
- 70?1 Brass
- 70?2 Chrome
- 70?4 Black

Inquiries on other finishes welcome

## PLATE DIAGRAMS



STANDARD PLATE: A38H

Plate Thickness: 1/4"