

ALGOOD.com
8000
SERIES

**LOW PROFILE
 CASTERS**

600 LBS
 capacity

FEATURES



**EXCELLENT
 FOR**

- Pianos & heavy equipment
- Floor protection & excellent mobility
- Business machines



OPTIONS

TSB Thumb Screw Brake
 (included in 8030 only)

PLATE DIAGRAMS

Standard 8022 Plate: **A27D**
 Standard 8030 Plate: **A32F**

D Plate Thickness: 3/32"
 F Plate Thickness: 5/32"



ALGOOD

KINGPIN: 5/16" rivet
RACEWAY: 3/16" diameter over and under race;
 hardened steel load bearings
BUSHING: Nylon, steel bearing
AXLE&NUT: 5/16" axle and nut
FINISH: Bright chrome
HARDENED: Washer
SPECIAL: Wide selection of specialty stems and plates



WHEEL		CASTER				PART NUMBER			Caster Weight (lbs)
Diameter	Tread Width	Capacity Lbs.	Bearing Type	Swivel Radius	Overall Height	Wheel Type	Swivel		
2" Dual Wheel	7/8"	150	Plain	1 13/16"	2 7/8"	ProTech™ Flat	S8022-***-PROF	0.82	
		160	Nylon			Soft Rubber	S8022-***-SR	1.10	
		200	Nylon			Hard Rubber	S8022-***-HR	1.10	
		200	Steel			Envirothane™	S8022-***-U	0.88	
		200	Steel			Envirothane™ Grey	S8022-***-UG	0.88	
2"	1 3/4"	200	Plain	1 13/16"	2 7/8"	Polyolefin	S8022-***-PO	0.84	
3"	1 13/16"	600	Roller	2 5/16"	4 1/16"	Phenolic	S8030-A32F-PH-RB-TSB-Z	2.50	

STEMS

**THREADED STEMS
 HEX NUT (8022 only)**

***	DIAMETER	LENGTH	TYPE
1/2-13X1 1/2HN	1/2"	1 1/2"	NC



**THREADED STEMS
 HEX WASHER (8022 only)**

***	DIAMETER	LENGTH	TYPE
1/2-13X1HW	1/2"	1"	NC
1/2-13X1 1/2HW	1/2"	1 1/2"	NC



ROUND STEMS (8022 only)

***	DIAMETER	LENGTH	TYPE
437SX1 5/16	7/16"	1 5/16"	Friction Ring

