



FREEDOM™ 700-1,200LBS

WHEELS



FEATURES

BEARINGS: Precision ball bearing
TEMPERATURE: -45°F to 230°F
COLOURS: Blue Tread, Aluminum Core
DUROMETER: 95 A Scale (40-45 D)

DESCRIPTION: Freedom™ wheel the aluminum core/envirothane crowned tread (chemically and mechanically bonded) is non-marking with debris-rejecting tread. This wheel allows for an easy, smooth and quiet ride. The Moldon Aluminum Urethane is excellent when looking for a wheel that will give maximum floor protection while carrying light or heavy weight loads. High degree of resistance to shock or vibration and rusting.

EXCELLENT FOR:

- Moist and wet environments
- Push/Pull Ease
- Smooth, Easy Rolling and Longevity
- Quiet Ride
- Absorbs Shock and Vibrations
- Prolonging of Equipment Life
- Factory Use
- Floor Protection
- Towline Applications
- Platform and Stock Trucks
- Outdoor Use and Heavy Loads
- Ease of Maneuverability
- Heavy Material Handling
- Abusive Applications



FREEDOM™

WHEEL						PART NUMBER			
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)	
4"	2"	750	2 3/16"	1/2"	-	Precision	W-7004-FDM-PB	1.43	
5"	2"	750	2 3/16"	1/2"	-	Precision	W-7005-FDM-PB	1.76	
6"	2"	1,000	2 3/16"	1/2"	-	Precision	W-7006-FDM-PB	2.67	
8"	2"	1,200	2 3/16"	1/2"	-	Precision	W-7008-FDM-PB	4.25	

OPTIONS:

- PBSS Stainless Steel Precision Bearing
- TG Thread Guard

SPECIAL:

- Non-marking
- Debris-Rejecting Tread
- Moisture friendly
- Maintenance free
- Light Weight
- High Load Capacity