



POLYOLEFIN WHEELS 25-900LBS



FEATURES

BEARINGS: Plain, Nylon, Delrin, Steel Roller, Caged Roller
TEMPERATURE: -20°F to 180°F
COLOURS: Black
DUROMETER: 65-70 D scale

DESCRIPTION: The Polyolefin wheel is light in weight, very economical and high impact strength. Non-marking, non-chipping, oil and chemical resistant, non-absorbent and steam cleanable wheel provides for floor protection.

EXCELLENT FOR:

- Factory use
- Platform trucks
- Resistant to most chemicals
- Easily maintained
- Economical



POLYOLEFIN



POLYOLEFIN



POLYOLEFIN



POLYOLEFIN (POX)

WHEEL

PART NUMBER

Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
							W-0160-PO	0.03
1 3/4"	Ball	75	1 5/8"	1/4"	-	Plain	W-0600-PO	0.12
2"	15/32"	25	9/16"	3/16"	-	Plain	W-0200-PO	0.03
	Ball	75	1 27/32"	1/4"	-	Plain	W-0650-PO	0.12
	7/8"	125	1"	1/4"	-	Plain	W-0800-PO	0.05
2 1/2"	7/8"	125	1"	1/4"	3/8"	Plain	W-0820-PO	0.11
	1 1/8"	200	1 3/8"	5/16"	3/8" * 1/2"	Plain	W-4025-PO	0.13
2 5/8"	1 1/2"	350	1 9/16"	12mm	-	Roller	W-54260-PO-RB	0.31
3"	7/8"	150	1"	1/4"	3/8" * 5/16" * 1/2"	Plain	W-0830-PO	0.15
	1 1/4"	150	1 3/8"	5/16"	3/8" * 1/2"	Plain	W-1030-PO	0.18
		300	1 9/16"	5/16"	-	Plain	W-1930-PO	0.18
		300	1 9/16"	3/8"	1/2"	Plain	W-4003-PO	0.18
	1 3/8"	250	1 9/16"	3/8"	-	Plain	W-4003-POHD	0.28
1 1/2"	400	1 5/8"	3/8"	5/16"	Steel	W-6203-PO	0.35	
	400	1 5/8"	1 3/16"	1/2" * 5/8"	Plain	W-6203-PO	0.27	
	400	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6203-PO-RB	0.57	
4"	1"	220	1 3/16"	5/16"	3/8" * 1/2"	Plain	W-1040-PO	0.22
	1 1/2"	250	1 9/16"	5/16"	3/8" * 1/2" * 5/8"	Steel	W-1940-PO	0.33
		275	1 11/16"	3/8"	1/2"	Plain	W-5004-PO	0.27
		400	1 5/8"	1 3/16"	-	Plain	W-6204-PO	0.35
		400	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6204-PO-RB	0.65
	2"	550	2 3/16"	1 3/16"	3/4"	Plain	W-7004-POX	0.42
550		2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7004-POX-RB	0.86	

OPTIONS:

- BB Ball Bearing
- DB Delrin Bearing
- NB Nylon Roller Bearing
- RB Roller Bearing
- RBC Caged Roller Bearing
- RBSS Stainless Steel Roller Bearing
- SSW Steel Side Washer
- SWH Heat-treated Side Washer
- T Through Bore (POX wheel only)
- TG Thread Guards

SPECIAL:

- Resistant to most chemicals
- Non-marking
- Moisture friendly
- Maintenance free

* Custom sizes available

POLYOLEFIN

WHEELS

WHEELS

CUSTOM SIZES AVAILABLE

WHEEL						PART NUMBER		
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
5"	1"	230	1 3/16"	5/16"	3/8" * 1/2"	Plain	W-1050-PO	0.29
	1 1/4"	350	1 3/8"	5/16"	3/8" * 1/2"	Plain	W-1950-PO	0.45
	1 1/2"	275	1 9/16"	3/8"	5/16" * 1/2"	Plain	W-5005-PO	0.53
		450	1 5/8"	1 3/16"	-	Plain	W-6205-PO	0.49
		450	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6205-PO-RB	0.79
	2"	375	2 1/4"	3/8"	1/2"	Plain	W-5305-PO	0.52
		650	2 3/16"	1 3/16"	3/4"	Plain	W-7005-POX	0.55
		650	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7005-POX-RB	0.99
6"	1 1/2"	550	1 5/8"	1 3/16"	-	Plain	W-6206-PO	0.89
		550	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6206-PO-RB	1.28
	2"	800	2 3/16"	1 3/16"	3/4"	Plain	W-7006-POX	0.71
		800	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7006-POX-RB	1.15
8"	2"	900	2 3/16"	1 3/16"	3/4"	Plain	W-7008-POX	1.15
		900	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7008-POX-RB	1.59