275-500lbs WHEELS

FEATURES

BEARINGS: Precision Ball Bearings TEMPERATURE: -20°F to 130°F COLOURS: Silver Core, Black Tread, UV Grey DUROMETER: 90 - 98 A Ścale

DESCRIPTION: Flat Free tires provide the bounce and load handling characteristics similar to pneumatic tires, except they never lose air. Flat Free are excellent for applications where floor and equipment is vital. The wheel provides for shock absorption, quiet operation and of rolling. Flat Free are light weight, non-marking moulded onto a heavy duty steel rim with high quality sealed ball bearings. For manual operation only.

FLAT FREE SAWTOOTH

EXCELLENT FOR:

- Uneven floors such as agricultural, . institutional and industrial
- Quiet Cushion ride
- Moist environments
- Shock and Vibration . .
- Prolonging eq
- Floor Protection •
- Platform and •
- Food Service
- Hotel Equipme
- Small waste b Factory use
- Textile carts

ADO21	veu	ihhi	lu

HUB SIZE:				
HUB LENGTH	CODE#			
2"	A			
2 1/4"	В			
2 1/2"	C			
2 5/8"	D			
3"	E			
3 1/4"				
4"	F			



libration equipment life		ISSI.									PART NUMBER	
tion d Large stock trucks e equipment	Diameter	Tread Width	Capacity Lbs.	Hub Length	Hub Type	Tire Colour	Standard Bore	Alternative Bore	Bearing Type	Tread Style	Part Number	Wheel Weight (lbs)
nent bins	6"	2"	275	2 1/2"	Center	Black	1/2"	-	Precision Ball	Sawtooth	W-7006-FFCC-PBB	1.70
lications		2"	280	2 1/2"	Center	Black	1/2"	-	Precision Ball	Sawtooth	W-7008-FFCC-PBB	1.70
	8"	2 1/2" (2.50x4)	275 275 275	2 ¹ /4" 3" 3"	Offset Center Center	Black Black Grey	5/8" 1/2" 1/2"	$\frac{1}{2}$ "* $\frac{3}{4}$ " $\frac{5}{8}$ "* $\frac{3}{4}$ " $\frac{5}{8}$ "* $\frac{3}{4}$ "	Precision Ball Precision Ball Precision Ball	Lug Lug Lug	W-7908-FFOB-PBB W-7908-FFCE-PBB W-7908-FFCEG-PBB*	2.70 2.70 2.70
CODE# A B C D	10"	3 1/2'' (4.10/3.50x4)	300 300 300 300 300	2" 2 ¹ /4" 3" 4"	Offset Offset Center Center	Black Black Black Black	5/8" 5/8" 5/8" 1/2"	$\frac{1/2}{1/2} = \frac{3}{4} = \frac{1}{2} = \frac{3}{4} = \frac{1}{2} = \frac{3}{4} = \frac{1}{2} = \frac{3}{4} = $	Precision Ball Precision Ball Precision Ball Precision Ball	Sawtooth Sawtooth Sawtooth Sawtooth	W-7910-FFOA-PBB W-7910-FFOB-PBB W-7910-FFCE-PBB W-7910-FFCF-PBB	3.75 3.75 3.75 4.00
E	12"	3 1/2" (4.10/3.50x6)	400	4"	Center	Black	1/2"	5/8 "* 3/4"	Precision Ball	Sawtooth	W-7912-FFCF-PBB	6.00
F H	16"	4'' (4.80/4.00x8)	500	4"	Center	Black	3/4"	1/2"* 5/8"	Precision Ball	Rib	W-7916-FFCF-PBB	8.00

SPECIAL:

4 1/4"

Non-marking under normal conditions Light weight Less downtime Maintenance Free Moisture friendly Many combinations of core and tread colours available Sealed Ball Bearing

* Special Order / Designs available by special order