



# PURTHANE™

WHEELS

125-1,200LBS



## FEATURES

**BEARINGS:** Precision ball bearing  
**TEMPERATURE:** -20°F to 180°F  
**COLOURS:** Black Tread, Aluminum Core  
**DUROMETER:** 80 (+/-5) A Scale

**DESCRIPTION:** Purthane™ wheel the aluminum core/purthane crowned tread (chemically and mechanically bonded) is non-marking with debris-rejecting tread. This wheel allows for an easy, smooth and quiet ride. The Moldon Aluminum Purthane is excellent when looking for a wheel that will give maximum floor protection while carrying light or heavy weight loads. High degree of resistance to shock or vibration and rusting.

### EXCELLENT FOR:

- Deflects Metal Debris
- Moist and Wet Environments
- Push/Pull Ease
- Smooth, Easy Rolling and Longevity
- Quiet Ride
- Absorbs Shock and Vibrations
- Prolonging of Equipment Life
- Factory Use
- Floor Protection
- Towline Applications
- Platform and Stack Trucks
- Outdoor Use and Heavy Loads
- Ease of Maneuverability
- Heavy Material Handling
- Abusive Applications



PURTHANE™

### WHEEL

### PART NUMBER

| Diameter | Tread Width | Capacity Lbs. | Hub Length | Standard Bore | Alternative Bore | Bearing Type | Part Number      | Wheel Weight (lbs) |
|----------|-------------|---------------|------------|---------------|------------------|--------------|------------------|--------------------|
| 3"       | 7/8"        | 125           | 1"         | 1/4"          | -                | Precision    | W-0830-PTN-PB-TG | 0.45               |
|          | 1 1/2"      | 600           | 1 3/4"     | 3/8"          | 1/2"             | Precision    | W-5403-PTN-PB    | 0.99               |
| 4"       | 1 1/2"      | 700           | 1 3/4"     | 3/8"          | 1/2"             | Precision    | W-5404-PTN-PB    | 1.39               |
|          | 2"          | 900           | 2 3/16"    | 1/2"          | -                | Precision    | W-7004-PTN-PB    | 1.34               |
| 5"       | 1 1/2"      | 700           | 1 3/4"     | 3/8"          | 1/2"             | Precision    | W-5405-PTN-PB    | 1.98               |
|          | 2"          | 1,000         | 2 3/16"    | 1/2"          | -                | Precision    | W-7005-PTN-PB    | 2.16               |
| 6"       | 2"          | 1,000         | 2 3/16"    | 1/2"          | -                | Precision    | W-7006-PTN-PB    | 2.76               |
| 8"       | 2"          | 1,200         | 2 3/16"    | 1/2"          | -                | Precision    | W-7008-PTN-PB    | 4.26               |

### OPTIONS:

PBSS Stainless Steel Precision Bearing  
 TG Thread Guard

### SPECIAL:

Non-marking  
 Debris-Rejecting Tread  
 Ergonomically Designed  
 Maintenance free  
 Maintain Floor Grip  
 High Load Capacity