

# VSP Wheel<sup>®</sup>

capacities up to **850 lbs**

VSP Mag

OPERATING TEMPERATURE: -22F to 176F Continuous  
-40F to 212 Intermittently

HARDNESS: 75-80 Shore A

Caster World's VSP Wheel features a Cushion Rubber tread pressed onto a Polypropylene Rim. This wheel can be fitted with an array of Ball and Delrin bearing solutions. Commonly used on Hand Trucks, and Appliance trucks throughout North America, the VSP has proved itself time and time again making it the solid choice in material handling cart applications.



VSP



VSP Spoke

## OPTIONS

### OPERATING CHARACTERISTICS:

- Puncture proof,
- Quiet rolling,
- Cushioned,
- Resilient,
- Excellent life expectancy,
- Low starting effort under load on uneven floors.

### BEARING OPTIONS:

- "BB" – Ball Bearings
- "BBHD" – Precision Ball Bearings
- "DB" – Flanged Delrin Bushing

### EXCELLENT FOR:

- Dollies
- Floor Protection
- Quiet Operation
- Stock Trucks
- Wheelers
- Hand Dollies

## VSP Wheel<sup>®</sup>

capacities up to **850 lbs**

Diameter (Ins.)	Tread Width	Bearing Type	Bore Size	Capacity (LBS)	Hub Color	Hub Length	Wheel Weight (lbs)	Part Number
8"	1 1/2"	Ball	1/2", 7/16", 5/8", 3/4"	400	Grey	2 1/4" Off Set	2.76	W-7008-VSPO-BB- **
8"	1 1/2"	Prec.Ball	1/2", 5/8", 3/4"	450	Grey	2 1/4" Off Set	2.76	W-7008-VSPO-BBHD- **
8"	1 1/2"	Delrin	1/2", 5/8", 3/4", 1"	300	Grey	2 1/4" Off Set	2.76	W-7008-VSPO-DB- **
8"	1 1/2"	Roller	3/4"	400	Grey	2 1/4" Centered	2.71	W-7008-VSPO-RB-3/4
8"	2"	Ball	1/2", 7/16", 5/8", 3/4"	400	Grey	2 1/4" Off Set	2.75	W-8X2.25-VSPO-BB- **
8"	2"	Prec.Ball	1/2", 5/8", 3/4"	450	Grey	2 1/4" Off Set	2.75	W-8X2.25-VSPO-BBHD- **
8"	2"	Delrin	1/2", 5/8", 3/4", 1"	350	Grey	2 1/4" Off Set	2.75	W-8X2.25-VSPO-DB- **
10"	2 3/4"	Ball	1/2", 7/16", 5/8", 3/4"	525	Black	2 1/4" Off Set	5.59	W-10X2.75-VSPOZ-BB- **
10"	2 3/4"	Prec.Ball	1/2", 5/8", 3/4"	575	Grey	2 1/4" Off Set	5.59	W-10X2.75-VSPOZ-BBHD- **
10"	2 3/4"	Delrin	1/2", 5/8", 3/4", 1"	475	Grey	2 1/4" Off Set	5.59	W-10X2.75-VSPOZ-DB- **
10"	3"	Ball	1/2", 7/16", 5/8", 3/4"	575	Grey	3 1/4" Centered	6.12	W-10X3-VSP-BB- **
12"	3"	Ball	1/2", 7/16", 5/8", 3/4"	750	Grey	3 1/4" Centered	8.13	W-12X3-VSP-BB- **
12"	3"	Prec.Ball	1/2", 5/8", 3/4"	800	Grey	3 1/4" Centered	8.13	W-12X3-VSP-BBHD- **
12"	3"	Delrin	1/2", 5/8", 3/4", 1"	700	Grey	3 1/4" Centered	8.13	W-12X3-VSP-DB- **
14"	1 3/4"	Ball	1/2", 7/16", 5/8", 3/4"	725	Black	3" Centered	10.37	W-14X3-VSP-BB- **
14"	1 3/4"	Prec.Ball	1/2", 5/8", 3/4"	775	Black	3" Centered	10.37	W-14X3-VSP-BBHD- **
14"	1 3/4"	Delrin	1/2", 5/8", 3/4", 1"	850	Black	3" Centered	10.37	W-14X3-VSP-DB- **
16"	1 3/4"	Ball	1/2", 7/16", 5/8", 3/4"	800	Black	3" Centered	13.18	W-16X3-VSP-BB- **
16"	1 3/4"	Prec.Ball	1/2", 5/8", 3/4"	750	Black	3" Centered	13.18	W-16X3-VSP-BBHD- **
16"	1 3/4"	Delrin	1/2", 5/8", 3/4", 1"	850	Black	3" Centered	13.18	W-16X3-VSP-DB- **

\*\* - Include Bearing Size